



**OFFICE OF THE SUPERINTENDING ENGINEER  
NATIONAL INSTITUTE OF TECHNOLOGY KARNATAKA, SURATHKAL**

Srinivas agar Post: 575 025 - MANGALURU - D.K.  
Phone: (0824) 2473029, Extn: 3028 & 3039, Fax: (0824) 2474000-023

**No. Stores/EI-NIQ/2022-23/SK -001**

Date: 21/07/2022

**NOTICE INVITING QUOTATIONS**

The National Institute of Technology Karnataka, Surathkal (in short - NITK, Surathkal or Institute) is an autonomous Institute of the Govt. of India [under the Ministry of Education] imparting technical and science education. The Institute intends to purchase the Insulation Tester as listed in the sheet enclosed. In this connection, sealed quotations are invited by the undersigned subject to the terms and conditions enumerated here under from the manufacturers/ authorized dealers/ agencies to reach this office on or before **10-08-2022 by 3:30 PM**. The quotations shall be opened on the same day if possible.

**Terms and conditions:**

1. The intending bidder shall quote his rates in the '**Quotation Format**' enclosed here with either in his letter head or using the same format. He shall sign each page with seal of the firm. Envelope super scripted as "**Quotation for the supply of Insulation Tester (Megger)** and addressed to as "The Superintending Engineer, NITK, Surathkal, Post Srinivasnagar, Mangalore – 575025" be sent to reach this office on or before the due date mentioned.
2. The GST registration number and the PAN number of the bidder shall be mentioned in the quotation. Quotation without this information will not be accepted.
3. Quotation may be dropped in the Tender Box kept in the office or may be sent by post/ courier. It is the responsibility of the bidder to make sure that the quotation is delivered in time. The quotations received after the due date will not be entertained.
4. The bidder shall specify the details of material for which the rate is offered by him.
5. The bidder shall mention the Warranty period of the material for which the rate is offered by him (if applicable).
6. The bidder shall quote the rates for materials including any Transportations and labours etc.
7. GST rate as applicable shall be mentioned clearly.
- 8. The rate quoted shall be valid for 90 days for its acceptance.**
9. The quotation/ bid shall be accepted or parts thereof depending on the lowest rate quoted for individual items. The bidder shall supply the materials accordingly.
10. The material (s) should be supplied within 7 days from the date of confirmation of acceptance of the quotation.
11. The material supplied should be strictly as per the specification specified, without which the material will be rejected.
12. In case of rejection of material, one more chance shall be given for its replacement with the material conforming to the specification specified. Failure to supply the material as per the specification will result in debarring the bidder for participation in bids for a minimum of one year.
13. No advance payment will be made. The payment shall be made within 30 days from the date of supply of material along with the bill. No interest will be paid for delayed payments if any.
14. The rate quoted should be firm. No claim for enhancement of rate is admissible after opening of the Quotations.
15. Terms and conditions stipulated in this Notice inviting conditions are binding on the bidder.

Sd-  
Superintending Engineer  
NITK, Surathkal

Name and Address of the Bidder:

GST registration number:

PAN number: -

Contact No:

Date:-

QUOTATION

To

The Superintending Engineer,  
Office of the Superintending Engineer,  
N.I.T.K., Surathkal.

	Description of the items	Brand/ Make	Qty	Rate	GST	Amt
1	<b>1550C FC 5 kV Digital Insulation Tester</b>  <b><u>Test Voltage (DC)</u></b> 250 V range: < 250 kΩ, > 50 GΩ 500 V range: < 500 kΩ, > 100 GΩ 1000 V range: < 1 MΩ, > 200 GΩ 2500 V range: < 2.5 MΩ, > 500 GΩ 5000 V range: < 5 MΩ, > 1 TΩ Bar graph range: 0 to 1 TΩ - 0 to 2 TΩ Leakage current measurement range:1 nA to 2 mA Capacitance measurement range:0.01 μF to 15.00 μF Timer range: 0 to 99 minutes Live circuit warning voltage: 30 V to 660 V AC/DC, 50/60 Hz Software specifications: basic software requires a PC running Windows XP, Windows Vista, Windows 7 or Windows 8.  <b><u>General specifications</u></b> Display size: 75 x 105 mm Power: 12 V lead-acid rechargeable battery, Input overload protection: 1000 volts Temperature (operating): -20°C to 50°C (-4°F to 122°F) Enclosure sealing: IP 40		1 No			

Seal and signature of the Bidder